

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 60 069 - 09 HH

Company CONEXA GmbH Präzisions-Armaturen
Vorm Berge 1
34346 Hann. Münden, GERMANY

Product Description COMPRESSION COUPLINGS, L-AND S-SERIES, MADE OF CARBON STEEL

Type 24° COMPRESSIONS FITTINGS ACCORDING TO DIN EN ISO 8434-1 / DIN 2353

Environmental Category None

Technical Data / Range of Application TECHNICAL DATA / MATERIALS

Pipes:
Precision steel pipes acc. to EN 10305-4 or equivalent.
Carbon steel 1.0255 (St37.4), 1.0580 (St52.4) or equivalent.

Union, Screw nut:
Carbon steel acc. to DIN 3859-1, Table 2 or equivalent.

RANGE OF APPLICATION
The COMPRESSION COUPLINGS L-AND S-SERIES are type approved for the use in piping systems according the Rules I - 1 - 2 Machinery Installations, Sec.11, Table 11.13 / 11.14, compression coupling, bite type, fire resistant.

Size and nominal pressure range PN according to page 2.

Test Standard VI-7-8- Regulations for the Performance of Type Approvals for Components and Systems of Mechanical Engineering and Offshore Technology: 2008

Documents - Test report no. S022.1/08, dated 2009-01-07
- Product catalogue 2007

Remarks Combination of carbon steel pipes and stainless steel unions and vice versa is not approved.

Valid until 2014-01-22

Page 1 of 2

File No. II.C.05

Hamburg, 2009-01-22

Type Approval Symbol



Germanischer Lloyd

i. V. Hanspeter Raschle
Hanspeter Raschle

i. A. P. Gierhan
Peter Gierhan

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 60 069 - 09 HH

PRESSURE RANGE

Carbon steel

Light Series (L)

Pipe O.D. Nom. Press.

[mm] [PN]

6 - 18 315

22 - 42 160

Heavy Series (S)

Pipe O.D. Nom. Press.

[mm] [PN]

6 - 14 630

16 - 30 400

38 315

TEMPERATURE RANGE

Carbon steel - 20°C to + 120°C

For service temperatures above 50°C (carbon steel) the reduction in pressure specified by the pipe manufacturer is to be observed.

The selection of the pipe unions for the corresponding service in view of temperature and pressure and the right installation are to be in accordance with the instructions of the manufacturer.

Valid until 2014-01-22

Page 2 of 2

File No. II.C.05

Hamburg, 2009-01-22

Type Approval Symbol



Germanischer Lloyd

i. V. Hanspeter Raschle
Hanspeter Raschle

i. A. P. Gierhan
Peter Gierhan

This certificate is issued on the basis of "Guidelines for the Performance of Type Approvals Part 1, Procedure".

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 75 126 - 09 HH

Company CONEXA GmbH Präzisions-Armaturen
Vorm Berge 1
34346 Hann. Münden, GERMANY

Product Description COMPRESSION COUPLINGS, L-AND S-SERIES, MADE OF STAINLESS STEEL

Type 24° COMPRESSIONS FITTINGS ACCORDING TO DIN EN ISO 8434-1 / DIN 2353

Environmental Category None

Technical Data / Range of Application TECHNICAL DATA / MATERIALS

Pipes:
Precision stainless pipes acc. to EN 10088 or equivalent.
Stainless steel 1.4571 (X6CrNiMoTi17-12-2) or equivalent.

Union, Screw nut:
Stainless acc. to DIN 3859-1, Table 2 or equivalent.

RANGE OF APPLICATION

The COMPRESSION COUPLINGS L-AND S-SERIES are type approved for the use in piping systems according the Rules I - 1 - 2 Machinery Installations, Sec.11, Table 11.13 / 11.14, compression coupling, bite type, fire resistant.

Size and nominal pressure range PN according to page 2.

Test Standard VI-7-8- Regulations for the Performance of Type Approvals for Components and Systems of Mechanical Engineering and Offshore Technology: 2008

Documents - Test report no. S022.2/08, dated 2009-04-29
- Product catalogue 2007

Remarks Combination of carbon steel pipes and stainless steel unions and vice versa is not approved.

Valid until 2014-05-26

Page 1 of 2

Type Approval Symbol



File No. II.C.05

Hamburg, 2009-05-26

Germanischer Lloyd

Hanspeter Raschle
Hanspeter Raschle

Peter Gierhan
Peter Gierhan

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 75 126 - 09 HH

PRESSURE RANGE

Stainless steel

Light Series (L)

Pipe O.D [mm]	Nom. Press. [PN]
6 - 18	315
22 - 42	160

Heavy Series (S)

Pipe O.D [mm]	Nom. Press. [PN]
6 - 14	630
16 - 30	400
38	250

TEMPERATURE RANGE

Stainless steel - 20°C to + 120°C

For service temperatures above 50°C (stainless steel) the reduction in pressure specified by the pipe manufacturer is to be observed.

The selection of the pipe unions for the corresponding service in view of temperature and pressure and the right installation are to be in accordance with the instructions of the manufacturer.

Valid until 2014-05-26

Page 2 of 2

File No. II.C.05

Hamburg, 2009-05-26

Type Approval Symbol



Germanischer Lloyd

Hanspeter Raschle
Hanspeter Raschle

Peter Gierhan
Peter Gierhan

This certificate is issued on the basis of "Guidelines for the Performance of Type Approvals Part 1, Procedure".